### PRODUCT SPECIFICATIONS

DOC NO. 240420SKP0AEN





### Key Features:

- ◆ Seamlessly connects to the SBS50 base station and integrates with Alexa. Long-press the emergency button to trigger an urgent alarm.
- ◆Easily switch security modes (disarm/home/away) by inputting a 4-digit PIN.
- ◆Supports up to 23 passwords (1 master code + 12 shared user codes + 10 guest codes), with customizable expiry dates.
- ◆Features entry and exit delay options for added convenience.
- ◆Schedule security mode changes with the calendar function for automatic adjustments.
- ◆Achieves a transmission range of at least 500m in open areas.
- ◆Simple installation with adhesive or screws.
- ◆Enjoy a 5-year product lifespan with replaceable batteries lasting at least 2 years

## Security Keypad SKP0A

### **Technical Specifications**



Power Supply	4 x AAA Replaceable Batteries		
Battery Life	≥2years (switch security modes twice daily via keypad, with customer-set 30s entry and exit delay)		
Product Life	≥ 5 years		
Operating Temperature	32-104 ° F (0-40 ° C)		
Operating Frequency	868MHz		
Арр	X-Sense Home Security (both Android and iOS supported)		
Product Weight	160g		
Product Dimensions	101x63x28mm		
Package Contents	1x Main Unit + 1x Pre-attached Mounting Plate (with double-sided adhesive) + 4x AAA Batteries + 1x Instruction Manual		

# Working Modes

Power On	Red LED flashes slowly once	Long beep once	
Network Configuration	Blue LED flashes rapidly continuously	Short beep once	
Successful Network Configuration	No LED indication Long beep once		
Normal Operation	No LED indication None		
Security Mode Prompt	Security Indicator:  In unconfigured state, all three mode lights on for 1s before turning off;  In configured state, the current mode press light on for 3s  In the other mode, lights remain off.		
Security Mode Switch	Security Indicator: Latest mode light on for 3s.	Long beep once	
Incorrect Password	Status Indicator: Short beep once Red light flashes rapidly twice. interval)		
Unauthorized Operation (Password set, but mode switch attempted without entering password)	Status Indicator:  Every time the security button is pressed, red light flashes rapidly twice.  Two short beeps on pressing the security button		
Arm Disregard Exception	Security Indicator: During a state, the expected mode light blinks once every 1s.	Short beep every 1 second, a total of 5 beeps	
	Security Indicator: Pressing the cancel button, the original mode light on for 3s.	None	
	Security Indicator: Pressing the confirm button, the expected mode light on for 3s.	Long beep once	
Entry Delay	Status Indicator: Red light flashes slowly continuously, and rapidly flashes during the last 10s countdown.  Continuous short beep, synced with flash rate		
Exit Delay	Security Indicator: Expected mode light slowly flashes continuously and rapidly flashes during the last 10s of the countdown.  Continuous short beep, synced with flash rate countdown.		



Alarm	Status Indicator: Red light rapidly flashing continuously.	Continuous short beep (can be set to flash only)	
Alarm Cancel	Status Indicator: Cancel successful, no indication. Security Indicator: Disarm mode light on for 3s.	Long beep once	
Emergency Alarm	Status Indicator: During operation confirmation, red light blinks once every 1 second for 3s; signal transmission successful, blue light rapidly flashes 3 times.	None	
Communication or Operation Failure (excluding password error)	Status Indicator: Red light rapidly flashes 3 times.	3 short beeps (100ms interval)	
Low Battery	Status Indicator: Red light blinks once every 60s.	None	
Keypad Test Passed	Status Indicator: Blue light illuminates for 3s.	None	

## **Ordering Information**

Part Number	Pack Quantity	Dimension	Weight	Units/Carton
SKPOA - 1 pack	1 x Alarm Unit	82 x 38 x 105 mm	14.5kgs	72 units

