

# PRODUCT SPECIFICATIONS

DOC. NO. 241014XS0FPMAEN

**X-SENSE**  
Your Trusted Home Safety Innovator



## Key Features:

- ◆ **Versatile Applications:** Operates as a standalone unit, wired interlinked unit, RF interlinked unit (with RF module)
- ◆ **Reliable Power Supply:** AC-powered with a 10-year sealed lithium battery, ensuring peace of mind during mains power outages.
- ◆ **Smart Installation Mode:** Provides immediate alerts if wiring is incorrect, simplifying setup.
- ◆ **Certified Safety:** Compliant with EN 14604 standards and BSI certified for trusted protection.
- ◆ **Alarm Memory Function:** Aids in the investigation of potential hazards by storing alarm events.
- ◆ **Advanced Optical Sensor:** High-performance, self-developed photoelectric sensor for accurate detection.

## Mains Powered Smoke Alarm

XS0F-PMA



## Technical Specifications

<b>Power Supply</b>	Input: 100-250 V (~), 25 mA, 50 Hz, 0.5 W
	Backup Battery Type: 3 V CR123A lithium battery x 1 (built-in 10-year non-replaceable)
<b>Maximum Service Life</b>	10 years
<b>Sensor Type</b>	Smoke: Photoelectric
<b>Safety Standards</b>	EN 14604:2005/AC:2008
<b>Operating Temperature</b>	4.4–37.8°C
<b>Operating Relative Humidity</b>	≤ 85% RH (non-condensing)
<b>Alarm Loudness</b>	≥ 85 dB at 3 m (10 ft) @ 3.2 ± 0.3 kHz pulsing alarm

<b>Silence Duration</b>	≤ 9 minutes
<b>Maximum Number of Interconnected Units</b>	Wired interconnection up to 18 units (Total cable length is limited to 300 m)
<b>Product Weight</b>	352 g
<b>Product Dimensions</b>	φ148 × 51.5 mm
<b>Package Contents</b>	1 × Alarm Unit + 3 × Screws + 3 × Anchor Plugs + 1 × User Manual + 1 × Mounting Bracket + 1 × QA Sticker + 1 × Dust Bag

## Working Modes

Mode		LED Indicator	Audible Alarm	Remarks
<b>Power-on</b>		The lights flash once in the sequence of red, green, and yellow.	None.	None.
<b>Standby Mode</b>	AC powered	Solid Green.	None.	None.
	Battery powered	Green LED flashes once every 60 seconds.	None.	None.
<b>Alarm Mode</b>	Initially triggered device	Red LED flashes 3 times every 4 seconds.	Sounds 3 times every 4 seconds.	None.
	Passively triggered device	None.	Sounds 3 times every 4 seconds.	None.
	Alarm off	Red LED flashes once every 1 second and lasts for 3 seconds.	None.	Smoke concentration is lower than that of alarm.

<b>Test Mode</b>	Test a single alarm	Red LED flashes 3 times every 4 seconds.	Sounds 3 times every 4 seconds.	Lasts for 2 cycles.
	Test all interconnected units (initially triggered device)	Red LED flashes once every second.	1 beep every second.	Press and hold the "Test/Silence" button without releasing.
	Test all interconnected units (other passively triggered devices)	Red LED flashes once every second.	1 beep every second.	None.
<b>Silence Mode</b>		Red LED flashes 3 times every 4 seconds.	None.	Lasts for 9 minutes.
<b>Memory Mode</b>	Within 24 hours	Red LED flashes once every 5 seconds.	None.	Lasts for 24 hours.
	After 24 hours	Red LED lights up for 2 seconds and go off.	None.	Occurs when self-test ended.
<b>Low Battery</b>		Yellow LED flashes once every 60 seconds.	1 beep every 60 seconds.	Only LED flashes when silenced.
<b>Device Malfunction</b>		Yellow LED flashes twice every 60 seconds.	2 beeps every 60 seconds.	None.
<b>End of Life</b>		Yellow LED flashes three times every 60 seconds.	3 beeps every 60 seconds.	Only LED flashes when silenced.
<b>Installation Mode</b>	Initially triggered device	Red LED flashes once every second.	1 beep every second.	None.
	Other passively triggered devices	Red LED flashes once every 10 seconds.	1 beep every 10 seconds.	None.

## Ordering Information

Part Number	Pack Quantity	Dimension	Weight	Units/Carton
XS0F-PMA - 1 pack	1 x Alarm Unit	155 x 155 x 65 mm	495 g	36 units